

SECTION 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name: CR-56P H3R (B)

Product Code: 850638 750638
850641 750641

Manufacturer: FUJIFILM HUNT CHEMICALS SINGAPORE PTE. LTD.
Co. Reg. No. 198901418E
15 Tuas Ave 7 Singapore 639270
Tel: (65) 6862 2116 Fax: (65) 6861 4829

Distributor:

SECTION 2 - COMPOSITION / INFORMATION ON INGREDIENTS

Ingredients (Mixture)

<u>Component</u>	<u>CAS No.</u>	<u>%by Weight</u>	<u>ACGIH TLV</u>
Sodium Sulfite	7757-83-7	0.5 - 1.5	NE
p-phenylenediamine Derivative	25646-71-3	30 - 50	NE
Water	7732-18-5	50 - 70	NE

SECTION 3 - HAZARDS IDENTIFICATION

Hazard Symbols:



Hazard Designation:

Xn - Harmful if swallowed.

Contains paraphenylenediamine derivative.

Risk Phrases:

R:42/43-52-53

May cause sensitisation by inhalation and skin contact.

Harmful to aquatic organisms.

May cause long term adverse effects in the aquatic environment.

Safety Phrases:

S: 24-37-60

Avoid contact with skin.

Wear suitable gloves.

This material and its container must be disposed of as hazardous waste.

SECTION 4 - FIRST AID MEASURES

Eye Contact:

In case of contact with eyes, rinse immediately with plenty of water and contact a doctor or Poisons Information Centre.

Skin Contact:

After contact with skin, wash immediately with plenty of water.

Ingestion:

If swallowed, contact a doctor or Poisons Information Centre immediately and show MSDS or label.

Inhalation:

Immediately remove victim to fresh air. Call a physician.

SECTION 5- FIRE FIGHTING MEASURES

Extinguishing Media:

Water spray, carbon dioxide, alcohol foam, dry chemicals.

Unsuitable Extinguishing Media:

None under normal conditions.

Fire Fighting Instructions:

Use water to keep fire-exposed containers cool and to dilute and flush spills from exposure.

Evacuate area and fight fire from a distance. Wear positive pressure demand breathing apparatus and protect eyes and skin. Use water to cool fire-exposed containers, to protect personnel and to disperse vapors and spills. Water runoff can damage the environment. Dike and collect water used to fight fire.

SECTION 6- ACCIDENTAL RELEASE MEASURES

Small Spills: Spills should be contained by, and covered with suitable absorbent material and removed for disposal

Large Spills: Prevent from entering into soil, waterways and groundwater

SECTION 7- HANDLING / STORAGE

Handling: Avoid contact with skin and eyes.
Use only in well ventilated area.
Wear suitable protective clothing, gloves and eye/face protection.

Storage: Keep out of reach of children.

SECTION 8- EXPOSURE CONTROL AND PERSONAL PROTECTION

Ventilation: Good general ventilation should be sufficient for most conditions.

Personal Protective Equipment:

Eye Protection: Chemical safety goggles.

Skin Protection: Neoprene gloves and apron.

Respiratory Protection: Required on all inadequately ventilated work stations.

SECTION 9- PHYSICAL AND CHEMICAL PROPERTIES

Appearance: liquid

Colour: Reddish-brown

Odour: irritating

Flammable Properties

Flash Point: N/Ap
Not flammable

Autoignition Temperature: N/Av
not flammable

Explosion Limits: Lower: N/Ap vol.%
Upper: N/Ap vol.%

Change in Physical State Boiling Point >100°C
Melting Point N/Av

Specific Gravity: 1.153

Vapour Pressure: N/Av

Viscosity: N/Av
like water

Solubility in water completely soluble

pH-value: 1.00 (25 deg C)

SECTION 10 - STABILITY AND REACTIVITY

Hazardous Polymerization: Will not occur

Hazardous Decomposition Products: .

Materials and Conditions to avoid: -

Further Information: None.

SECTION 11 - TOXICOLOGICAL INFORMATION

Product Information:

AcuteOral (The oral LD50): >500 mg/kg

Test Animal: Rat (Slc:Wister)

AcuteDermal (The dermal LD50): N/Av

Test Animal: -----

Acute Overexposure:

Primary Skin Irritation Index 3.58

(Primary irritation index)

Test Animal: Rabbit (Japanese)

Primary Eye Irritation Index 16.00

(Single ocular instillation)

Test Animal: Rabbit (Japanese)

Further Information: N/Av

Chronic Overexposure: N/Av

Ingredients Information:

<u>Component</u>	<u>CAS No.</u>	<u>Acute Oral LD 50 (mg/kg)</u>	<u>Test Animal</u>
Sodium Sulfite	7757-83-7	820	Mice
p-phenylenediamine Derivative	25646-71-3	-	N/Av

SECTION 12- ECOLOGICAL INFORMATION

Ecotoxicity Data: N/Av

Chemical Fate Data: N/Av

<u>Component</u>	<u>CAS No.</u>	<u>Fish Toxicity</u>	<u>Fish Organism</u>
Sodium Sulfit	7757-83-7	N/Av	-
p-phenylenediamine Derivative	25646-71-3	LC50:N/Av	-

SECTION 13- DISPOSAL CONSIDERATION

Disposal Regulations in Singapore:

Dispose off in accordance to the Environmental Public Health (Toxic Industrial Waste) Regulations under the Environmental Pollution Control Act 1999

Disposal Regulations Overseas:

Dispose off in accordance with all applicable local or national regulations

SECTION 14 - TRANSPORT INFORMATION

Marine Transportation

Class: Class 8, Corrosive

UN-No.: 3265

IMDG-code page: 8147-1

EMS: 8-15

MFAG: 760

Packing group: III

Sea Transport Statement Do not allow any contact with light metals ----- danger of corrosion

Proper shipping Name: Corrosive Liquid, Dangerous Goods under 'LTD QTY' (contains organic amine sulphate).



Issue Date: 8 May 2007

MSDS Number: 01B

Pdt DB No. 7361DB

Page No.: 6 of 6

Air Transportation

Class: Class 8, Corrosive

UN-No.: 3265

Proper Shipping Name: Corrosive Liquid, Dangerous Goods under 'LTD QTY'
(contains organic amine sulphate).

Subsidiary risk: -----

Labels: Corrosive

Packing group: III

Passenger aircraft: Packing Instruction 818 Max. 5L

Cargo aircraft only: Packing Instruction 820 Max. 60L

Further Information: Do not allow any contact with light metal ----- danger of corrosion



SECTION 15 - REGULATORY INFORMATION

Singapore Law

Environmental Public Health Act (Chapter 95) Rev. Ed. 1988

Part III : Disposal and Treatment of Industrial Wastes

The Environmental Pollution Control Act, 1999

Part V: Water Pollution Control

Part VII: Hazardous Substances Control

Water Pollution Control and Drainage Act, (Chapter 348) Rev. Ed. 1983

Part IV: Water Pollution Control

Part V: Sewerage

Workplace Safety and Health Act (Chapter 354A) Rev. Ed. 2007

Part V: General Duties of Persons at Workplaces

Workplace Safety and Health (General Provisions) Regulations 2006

Part IV: Special Provisions Relating to Health, Safety and Welfare

First Schedule: Permissible Exposure Limits of Toxic Substances

SECTION 16 - OTHER INFORMATION

This information is provided without warranty. The information is believed to be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.